
INSTRUCTIONS WESTERN HAND FLUSH KIT ASSEMBLY

INTRODUCTION

Portable restrooms and accessory kits must be assembled according to approved assembly procedures. Avoid variations in assembly procedures could adversely affect product life and warranty. HARDWARE

 \wedge



✓1 #18473 BOWL ASSY, FLUSH−II			
12	15537	2	SCREW, #4 X 3/8 FH STNLS
11	14403	1	NOZZLE, SINGLE SLOT FLUSH
10	10451	1	ELBOW, 90 3/4 FPT X 1 INS PVC
		1	BOWL, FLUSH
#15643 KIT, H/FLSH WEST/BOWL RECIR			
9	17331	1	WEIGHT, TURBO RECIRC FILTER
8	11261	1	TIE, WIRE 6in
7	16949	1	SCREEN, TURBO RECIRC FILTER
6	19173	1	PUMP, BILGE W/ELBOW
	15644	1	INSTRUCTION, WEST H/FLSH RECIR
4	14384	52	HOSE, #44 FLEX
3	15143	1	FILTER, RECIRCULATING FLUSH
2	12588	4	CLAMP, WORMDRIVE #12
1	18473	1	BOWL ASSY, FLUSH-II

TOOLS *Drill Elec/Cordless *5/16 Drill Bit *3-1/2 Hole saw *Flat blade Screwdriver *Utility Knife *Pencil

1. Drill Pump Mounting Holes: Find the tank that you will be mounting the Hand Flush kit too. Measure to center as shown and mark with pencil. With 3-1/2 hole saw, drill through tank wall. Center top plate (this will be with #19173 pump) over 3-1/2 hole. Mark the (4) holes with pencil. Remove plate and drill (4) with 5/16 drill bit. On some tanks you may have to cut a slot in the opening for the hose and elbow clearance. Do that at this time as shown.

